




**Part Number:** **FS-250014-2**  
 Revision 20161018 - Generated 2016-Oct-26



<b>OD</b>	(nom. - bare core) (max. - after coating)	63.50 mm 64.77 mm	2.500 in 2.550 in
<b>ID</b>	(nom. - bare core) (min. - after coating)	31.37 mm 30.48 mm	1.235 in 1.200 in
<b>Ht</b>	(nom. - bare core) (max. - after coating)	25.00 mm 25.90 mm	0.984 in 1.020 in
<b>Mass</b>	(approximate)	310 grams	
<b>Magnetic Dimensions</b>	A <sub>e</sub> - Eff. Mag. Cross Section	3.89 cm <sup>2</sup>	
	L <sub>e</sub> - Eff. Mag. Path Length	14.314 cm	
	V <sub>e</sub> - Eff. Core Volume	55.8 cm <sup>3</sup>	
	WA - Min. Eff. Window Area	7.30 cm <sup>2</sup>	
	sa - Surface Area	150 cm <sup>2</sup>	
	mlt - mean length per turn	10.1 cm	
	<b>Inductance</b>	μ <sub>i</sub> (reference)	14
A <sub>L</sub> value (nominal)		48 nH/N <sup>2</sup>	
Test Winding		N=100, #18 AWG	
Frequency		10 kHz	
Voltage on Agilent 4284A		1.7 V	
AL tolerance		±8%	
<b>Core Loss</b>	$\text{Core Loss (mW/cm}^3) = \frac{f}{\frac{a}{Bpk^3} + \frac{b}{Bpk^{2.3}} + \frac{c}{Bpk^{1.65}}} + d \cdot Bpk^2 \cdot f^2$		
	where B <sub>pk</sub> expressed in gauss, f expressed in hertz, and: a=1.000E+06, b=6.131E+07, c=2.047E+06, d=6.095E-14		
	B <sub>pk</sub>	300 G	
	frequency	100 kHz	
	Core Loss (nominal)	399 mW/cm <sup>3</sup>	
Core Loss (maximum)	459 mW/cm <sup>3</sup>		
<b>DC Saturation</b>	$\% \mu_i = \frac{1}{a + b \cdot H^c} + d$		
	where H expressed in oersteds, and: a=1.000E-02, b=2.600E-07, c=1.557, d=0.000		
	H <sub>DC</sub>	200 Oe	
	Percent Initial Perm(nom.)	90.9%	
<b>Coating/Pkg</b>	Coating Type:	Blue Epoxy	
	Voltage Breakdown (min.)	1000 Vrms	
	Limit	0.1 mA, 5 s	
	Package Quantity	27 Pcs/Box	

<b>Winding Table</b>	<b>Wire Size</b>	AWG	8	10	12	14	16	18	20	22	24	26	28
		mm	3.150	2.500	2.000	1.600	1.250	1.000	0.800	0.630	0.500	0.400	0.315
	<b>Single Layer</b>	Turns	23	29	37	47	59	74	93	116	145	182	227
		Rdc(Ω)	4.8 m	9.6 m	19.5 m	39.4 m	78.6 m	156.9 m	313.5 m	622.0 m	1.2	2.5	4.9
<b>Full Winding</b>	Turns	38	59	91	142	219	339	525	813	1,258	1,947	3,013	
	Rdc(Ω)	7.9 m	19.6 m	48.0 m	119.0 m	291.9 m	718.6 m	1.8	4.4	10.7	26.4	65.0	

