



Part Number: **FS-401040-2**
Revision 20160816 - Generated 2016-Aug-16



OD	(nom. - bare core)	101.60 mm	4.000 in										
	(max. - after coating)	102.87 mm	4.050 in										
ID	(nom. - bare core)	57.15 mm	2.250 in										
	(min. - after coating)	55.75 mm	2.195 in										
Ht	(nom. - bare core)	13.59 mm	0.535 in										
	(max. - after coating)	14.86 mm	0.585 in										
Mass	(approximate)	480 grams											
Magnetic Dimensions	A _e - Eff. Mag. Cross Section	2.97 cm ²											
	L _e - Eff. Mag. Path Length	24.271 cm											
	V _e - Eff. Core Volume	72.1 cm ³											
	WA - Min. Eff. Window Area	24.4 cm ²											
	sa - Surface Area	293 cm ²											
	mlt - mean length per turn	10.5 cm											
	Inductance	μ _i (reference)	40										
Core Loss	A _L value (nominal)	62 nH/N ²											
	Test Winding	N=140, #18 AWG											
	Frequency	10 kHz											
	Voltage on Agilent 4284A	1.8 V											
	AL tolerance	±8%											
	$\text{Core Loss (mW/cm}^3\text{)} = \frac{f}{\frac{a}{B_{pk}^3} + \frac{b}{B_{pk}^{2.3}} + \frac{c}{B_{pk}^{1.65}}} + d \cdot B_{pk}^2 \cdot f^2$ <p>where B_{pk} expressed in gauss, f expressed in hertz, and: a=1.000E+06, b=3.071E+08, c=3.524E+06, d=5.634E-14</p>												
DC Saturation	B _{pk}	1000 G											
	frequency	50 kHz											
	Core Loss (nominal)	780 mW/cm ³											
	Core Loss (maximum)	897 mW/cm ³											
Coating/Pkg	$\% \mu_i = \frac{1}{a + b \cdot H^c} + d$ <p>where H expressed in oersteds, and: a=1.000E-02, b=6.314E-08, c=2.151, d=0.000</p>												
	H _{DC}	200 Oe											
	Percent Initial Perm.(nom.)	64.0%											
	Percent Initial Perm.(min.)	54.5%											
Winding Table	Coating Type:	Blue Epoxy											
	Voltage Breakdown (min.)	1000 Vrms											
	Limit	0.1 mA, 5 s											
	Package Quantity	16 Pcs/Box											
	Wire Size	AWG	8	10	12	14	16	18	20	22	24	26	28
Single Layer	mm	3.150	2.500	2.000	1.600	1.250	1.000	0.800	0.630	0.500	0.400	0.315	
	Turns	44	56	70	88	110	138	172	215	268	335	417	
Full Winding	Rdc(Ω)	9.5 m	19.2 m	38.1 m	76.2 m	151.5 m	302.3 m	599.2 m	1.2	2.4	4.7	9.3	
	Turns	128	198	306	474	733	1,135	1,756	2,719	4,208	6,512	10,079	
	Rdc(Ω)	27.6 m	67.8 m	166.6 m	410.5 m	1.0	2.5	6.1	15.1	37.1	91.3	224.6	

